

## NRL 0280/0750 heat pumps

### R410A



**AERMEC**

participates in the EUROVENT programme for: LCP Check ongoing validity of certificate online:  
[www.eurovent-certification.com](http://www.eurovent-certification.com)

Variable Multi Flow

VMF



- **EUROVENT EFFICIENCY'S CLASS "A" IN HEATING OPERATION**
- **HIGH EFFICIENCIES ALSO AT PARTIAL LOADS**
- **FAST AND EASY INSTALLATION**

#### Characteristics

Reversible heat pumps for external installation for the production of chilled/heated water with high performance and low electric absorption scroll compressors, axial fans, external copper coils with aluminium fins, system-side plate heat exchanger.

In the units with desuperheater, but in cooling-only operation, it is possible to produce free hot water. The basement, the structure and the panelling are in steel treated with polyester anti-corrosion paint.

#### Version

- NRL\_H** Standard heat pumps
- NRL\_HL** Standard heat pumps Low noise version
- NRL\_HA** High efficiency version
- NRL\_HE** High efficiency version Low noise version

**Operating limits:** Work at full load down to -15°C external air temperature in winter season, up to 46°C in summer season. Hot water production up to 55°C (for more

details please refer to the technical documentation)

- Units with two refrigerant circuits designed to reach the maximum performance at full load, granting high efficiencies also at partial loads and assuring continuity in case of stop of one of the two circuits.
- Flow switch, water filter and high and low pressure transducer are standard supplied.
- Possibility of integrated hydronic kit which includes the main hydraulic components; it is available in different configurations with or without buffer tank, one or two pumps high and low head.
- Microprocessor adjustment, with keyboard and LCD display, for easy consultation and intervention on the unit via a menu available in several languages. Adjustment includes complete management of the alarms and their log.
- The presence of a programmable timer allows setting time bands of operation and a possible second

set-point

- The temperature control takes place with the integral proportional logic, based on the water output temperature.
- Night Mode: it is possible to set a silenced operation profile. Perfect for night operation, since it guarantees greater acoustic comfort in the evenings, and a high efficiency in the time of greater load.

**Night Mode is standard on all low noise versions. For all other versions either the DCPX accessory or "J" inverter fan must be specified to allow Night Mode to operate.**

#### Accessories

- **AER485P1:** RS-485 interface for supervising systems with MODBUS protocol.
- **PGD1:** Simplified remote panel. Allows control of basic unit functions and alarm notification.
- **MULTICHLILLER\_PCO:** Control system to switch the individual chillers on and off, and command them, in a system in which several units are installed in parallel, always ensuring a constant delivery to the evaporators.
- **AERWEB300:** Accessory AERWEB allows remote control of a chiller through a common PC and an ethernet connection over a common browser; 4 versions available:  
AERWEB300-6: Web server to monitor and remote control max. 6 units in RS485 network;  
AERWEB300-18: Web server to monitor and remote control max. 18 units in RS485 network;

remote control max. 18 units in RS485 network;  
AERWEB300-6G: Web server to monitor and remote control max. 6 units in RS485 network with integrated GPRS modem;  
AERWEB300-18G: Web server to monitor and remote control max. 18 units in RS485 network with integrated GPRS modem  
• **DCPX:** Device for condensation temperature control, with continuous speed modulation of fans by using a pressure transducer.  
• **GP:** Protective grille. Condenser coil external protection against accidental or hail damage.  
• **VT:** anti-vibration support, to be fitted below the sheet metal base of the unit.

- **DRE:** Current soft starter device, Available only with power supply 400V/3N.
- **RIF:** Power factor correction. Connected in parallel to the motor allowing about 10% reduction of input current
- **PRM1:** It is a manual pressure switch electrically wired in series with the existing automatic high pressure switch on the compressor discharge pipe.
- **COMPATIBILITY with the VMF SYSTEM** For more information on the system refer to the manual.

#### Accessories factory fitted only

## Compatibility of accessories

Mod. NRL	Vers.	0280	0300	0330	0350	0500	0550	0600	0650	0700	0750
<b>AER48SP1</b>	all	.	.	.	.	.	.	.	.	.	.
<b>PGD1</b>	all	.	.	.	.	.	.	.	.	.	.
<b>MULTICHLILLER_PCO</b>	.	.	.	.	.	.	.	.	.	.	.
<b>AERWEB300</b>	all	.	.	.	.	.	.	.	.	.	.
	(1)	H	-	-	-	64	64	64	64	64	64
<b>DCPX</b>	(1)	HL			inverter fans		standard	standard	standard	standard	standard
	(1)	HA	-	-	-	64	64	64	64	65	65
	(1)	HE			inverter fans		standard	standard	standard	standard	standard
	(1)	H	-	-	-	-	-	-	-	-	-
<b>DCPX Increased fans (M)</b>	(1)	HL	63	63	63	63	-	-	-	-	-
	(1)	HA	-	-	-	-	-	-	-	-	-
	(1)	HE	63	63	63	63	-	-	-	-	-
<b>GP</b>	(2)	H-HL	3	3	3	3	2 (x2)	2 (x2)	2 (x2)	2 (x2)	10 (x3)
	(2)	HA-HE	3	4	4	4	2 (x2)	2 (x2)	2 (x2)	2 (x2)	10 (x3)
<b>VT (00-P1-P2-P3-P4)</b>		H-HL	17	17	17	17	13	13	13	13	23
		HA-HE	17	17	17	17	13	13	13	13	23
<b>VT (01...10)</b>		H-HL	13	13	13	13	10	10	10	10	23
		HA-HE	13	13	13	13	10	10	10	10	23

Accessories factory fitted only											
<b>DRE</b>	400V/3N	281	301	331	351	501	551	601	651	701	751
<b>RIF</b>	all	50	50	50	51	52	52	53	53	53	53
<b>PRM1</b>	all	.	.	.	.	.	.	.	.	.	.

(1) Standard in the models with desuperheater; In the low noise versions; Not necessary fields with ventilarori inverter

(2) (x2)(x3) the number in brackets indicates the quantity to order

## Unit Configurator

By suitably combining the numerous options available it is possible to configure each model in such a way as to meet the most demanding of system requirements.

Field	Code		J Inverter
<b>1,2,3</b>	<b>NRL</b>		
<b>4,5,6,7</b>	<b>Size</b>	0280-0300-0330-0350-0500-0550-0600-0650-0700-750 (3)	
<b>8</b>	<b>Expansion valve</b>	<ul style="list-style-type: none"> <li>° Standard (leaving water temperature down to 4°C)</li> <li>X Electronic expansion valve (leaving water temperature down to 4°C) contact head office for lower temperatures (4)</li> </ul>	
<b>9</b>	<b>Model</b>		<b>Power supply</b>
	<b>H</b> Heat pumps		° 400V/3N/50Hz with circuit breakers
<b>10</b>	<b>Heat recovery</b>	<ul style="list-style-type: none"> <li>° Without recovery</li> <li>D With Desuperheater (5)</li> </ul>	1 220V/3/50Hz with circuit breakers
<b>11</b>	<b>Version</b>	<ul style="list-style-type: none"> <li>° Compact</li> <li>L Compact low noise</li> <li>A High efficiency</li> <li>E High efficiency in low noise operation</li> </ul>	<b>Hydronic kit (7)</b>
<b>12</b>	<b>Coil</b>	<ul style="list-style-type: none"> <li>° In aluminium</li> <li>R In copper</li> <li>S In tinned copper</li> <li>V In painted aluminium-copper (epoxy paint)</li> </ul>	<b>00</b> Without hydronic kit <b>01</b> n°1 low head pump and buffer tank <b>02</b> n°2 low head pump and buffer tank <b>03</b> n°1 high head pump and buffer tank <b>04</b> n°2 high head pump and buffer tank <b>05</b> n°1 low head pump and buffer tank (with holes for immersion heaters) <b>06</b> n°2 low head pump and buffer tank (with holes for immersion heaters) <b>07</b> n°1 low high pump and buffer tank (with holes for immersion heaters) <b>08</b> n°2 low high pump and buffer tank (with holes for immersion heaters) <b>09</b> double hydraulic circuit <b>10</b> double hydraulic circuit with holes for immersion heaters <b>P1</b> n°1 low head pump <b>P2</b> n°2 low head pump <b>P3</b> n°1 high head pump <b>P4</b> n°2 high head pump
<b>13</b>	<b>Fans (6)</b>	<ul style="list-style-type: none"> <li>° Standard</li> <li>M Increased</li> </ul>	

(3) The size 0280-0300-0330-0350 only available in low noise version "HL/HE" with inverter fans

(4) Options D are not compatible with option X

(5) The desuperheater can be used exclusively in the cold operation

(6) **On / off fan Standard**, standard sizes up 0500 to 0750

**On / off fan Increased**, option for size up 0280 tu 0350

**Fans Inverter**, standard sizes from 0280 to 0350, with no static pressure

**Fans Inverter**, option for sizes from 0500 to 0750 with static pressure

(7) Buffer tanks with holes for additional heaters are supplied from factory with plastics caps of protection, before system's loading, where the installation of one or all the heaters is not provided, it is mandatory to replace plastic caps with special caps, which are commonly available in the market.



## Technical Data

		280	300	330	350	500	550	600	650	700	750
<b>Electrical data</b>											
Total input current (cooling)	H (5)	A	/	/	/	63,0	67,0	81,0	88,0	100,0	122,0
	HL (5)	A	36,0	40,0	44,0	51,0	70,0	75,0	90,0	99,0	111,0
	HA (5)	A	/	/	/	55,0	60,0	71,0	77,0	90,0	113,0
	HE (5)	A									
Total input current (heating)	H (5)	A	/	/	/	60,0	63,0	76,0	82,0	95,0	113,0
	HL (5)	A	33,0	38,0	41,0	50,0	60,0	63,0	76,0	82,0	95,0
	HA (5)	A	/	/	/	55,0	59,0	72,0	82,0	88,0	113,0
	HE (5)	A									
Maximum current (FLA)	(5)	A	46	53	58	63	76	81	100	112	122
Starting current (LRA)	(5)	A	155	184	190	200	214	220	232	243	261
<b>Scroll Compressor</b>	Compressors / Circuit	n°	2/2	2/2	2/2	2/2	3/2	3/2	4/2	4/2	4/2
Refrigerant	Type						R410A				
<b>Heat exchanger system side</b>											
Exchanger	Type/n°						Plate/1				
hydraulic connections (In/Out)	Ø	2½"	2½"	2½"	2½"	2½"	2½"	2½"	2½"	2½"	3"
<b>Axial fans</b>											
Fans	H	Type/n°	/	/	/	/	std/2	std/2	std/2	std/2	std/3
	HL	Type/n°	Inverter/4	Inverter/6	Inverter/6	Inverter/6	std/2	std/2	std/2	std/2	std/3
	HA	Type/n°	/	/	/	/	std/2	std/2	std/2	std/3	std/3
	HE	Type/n°	Inverter/6	Inverter/8	Inverter/8	Inverter/8	std/2	std/2	std/2	std/3	std/3
Air flow rate (cooling)	H	m³/h	/	/	/	/	39400	39400	39400	37500	50200
	HL	m³/h	14000	20000	20000	20000	28400	28700	28700	27400	28100
	HA	m³/h	/	/	/	/	37000	37000	36500	36500	48000
	HE	m³/h	20000	26000	26000	26000	20200	21100	21400	22400	31900
<b>Sound data (cooling)</b>											
Sound power level	H	dB(A)	/	/	/	/	82	82	82	83	85
Sound pressure level	H	dB(A)	/	/	/	/	50	50	50	51	53
Sound power level	HL	dB(A)	73	74	74	75	77	77	78	78	80
Sound pressure level	HL	dB(A)	41	42	42	43	45	45	46	46	48
Sound power level	HA	dB(A)	/	/	/	/	82	82	82	83	85
Sound pressure level	HA	dB(A)	/	/	/	/	50	50	50	51	53
Sound power level	HE	dB(A)	74	75	75	76	74	74	75	77	77
Sound pressure level	HE	dB(A)	42	43	43	44	42	42	43	45	45

(5) Unit standar configuration without hydronic kit


**Sound power** Aermec determines sound power values on the basis of measurements made in accordance with UNI EN ISO 9614-2, as required for Eurovent certification.

**Sound pressure** Sound pressure in free field, at 10 m distance from the external surface of the unit (in accordance with UNI EN ISO 3744).


**Note:** For more information, refer to the selection program or the technical documentation available on the website [www.aermec.com](http://www.aermec.com)

## Dimensions (mm)


NRL 0280 HL




NRL 0300-0330-0350 HL




NRL 0500-0550-0600-0650-0700 H/HL




NRL 0280 HE



NRL 0300-0330-0350 HE




NRL 0500-0550-0600-0650 HA/HE



NRL 0700 HA/HE

NRL 0750 H/HL/HA/HE



Mod. NRL	Vers.	0280	0300	0330	0350	0500	0550	0600	0650	0700	0750
Height (mm)	A	Alls	1606	1606	1606	1875	1875	1875	1875	1875	1975
Width (mm)	B	Alls	1100	1100	1100	1100	1100	1100	1100	1100	1500
Length (mm)	C	H/HL	2450	2450	2450	3010	3010	3010	3010	3010	4350
Weight empty	kg (6)	H/HL	713	724	731	740	913	917	1016	1130	1142
		HA/HE	730	795	805	811	1099	1103	1204	1212	1487
											1748

(6) Unit standar configuration without hydronic kit

Aermec reserves the right to make all modification deemed necessary for improving the product at any time with any modification of technical data.

**Aermec S.p.A.**  
Via Roma, 996 - 37040 Bevilacqua (VR) - Italy  
Tel 044263111 - Fax 044293577  
[www.aermec.com](http://www.aermec.com)