


FABRIC


Opti-X[™] is a custom designed fabric used for targeted air dispersion to meet the quality and performance standards demanded in critical cleanroom environments.

- **Antimicrobial Construction:** Polyester with antimicrobial treatment proven to remain effective beyond 75 laundering cycles
- **Antistatic Construction:** Filament polyester with interwoven electrostatic-dissipative (ESD) yarns to remain effective 250 laundering cycles or the life of the product
- **Non-Shed Clean Room Grade:** Class 5 ISO or higher filament/filament polyester weave
- **Inlet:** Clean design with no cover belt and quick disconnect


COLOR OPTIONS



WHITE



SILVER



CUSTOM

* Note: Colors may vary. No two dye lots are the exact same color.

SPECIFICATIONS

Weave:	Non-Shed Clean Room Grade Fire Retardant Polyester
Antimicrobial:	EPA registered anti-microbic good beyond 75 washes
Antistatic:	Interwoven ESD Yarns with surface resistance of 1x10 ⁶ -1x10 ⁸ ohms/sq AATCC-76
Weight:	3.1 oz/yd ² (98g/m ²)
Porosity:	3 CFM/ft ² @ 0.5" w.g (15.2 L/s/m ² @ 125Pa)
Codes:	Classified by Underwriters Laboratories in accordance with the requirements of: <ul style="list-style-type: none">• NFPA 90A• UL 2518• UL-C (Canada)• AS/NZS 1530.3-1999 (Australia / New Zealand)