

# DATA SHEET

## RT-3000-P

### NEMA 4X DUCT SMOKE DETECTOR



#### PRODUCT DESCRIPTION

The RT-3000-P is a photoelectric weather tight duct smoke detector. The weathertight, NEMA 4X rated, corrosion resistant enclosure, coupled with extended temperature listings, allow installation in the widest possible range of indoor/outdoor environments.

#### AGENCY LISTING



#### PRODUCT FEATURES

- Patented **No-Tools Required** front or rear loading, and sampling/exhaust tubes removing
- Patented **Test Port Valve** allows for aerosol smoke testing without cover removal
- NEMA 4x rated watertight and corrosion resistant enclosure for hazardous indoor and outdoors applications
- Patented Maintenance Mode offers 3-minute interval for test and maintenance functions with no extra trouble reports to the system (auto shut-off upon cover latch engagement)
- No-tools terminal blocks for easier wiring with built-in test meter probe access
- Detector head's LED indicates for normal status (flashing light), alarm status (solid state), or trouble (yellow light)
- Raised LED indicators have 180 visibility
- Magnet test capability (magnet included)
- All gaskets are permanently attached and pre-installed
- Unit's PCB board includes green pilot, red alarm yellow for trouble visual indicators, visible with cover in place
- Cover tether keeps cover with detector and a single cover latch releases the cover from the unit
- Reset switch is also an alarm test switch
- Operating voltages: 230VAC, 115VAC, 24VAC, 24VDC
- Relay contacts:
  - Two sets of 10A form C alarm contacts
  - One set of 10A form C trouble contacts
  - One set of 1A form "A" alarm contacts and one set of 7A form "B" trouble contacts for FACU interface
- Standard "plug-in" UL268 photoelectric heads with advances internal dust filtering design
- No additional screens or filters to clean
- Complete wiring details permanently attached to unit
- Low-Flow Technology (between 100-4000 ft./min)
- Listed for high-temperature applications
- Compatible with building automation and fire alarm systems

#### Sampling Tubes

Sampling tubes must be ordered separately and are required for proper installation

##### FAST Tubes



PLASTIC ADAPTOR  
LOCKS IN TUBES



INSERT ADAPTOR, INTERCONNECT TUBES  
& TURN TOWARD AIRFLOW



INSERT TUBES & TURN  
TOWARD AIRFLOW

LOCK TUBES USING  
RETENTION CLIP

##### STN- Series Metal Tubes

Part	Length	Duct Width
STN-1.0	10" Tube	0-1 ft.
STN- 2.5	2.5' Tube	1-3 ft.
STN- 5.0	5.0' Tube	3-5 ft.
STN- 10.0	10.0' Tube	5-10 ft.

# PRODUCT SPECIFICATIONS

<b>MODEL NUMBER:</b>	RT-3000-P Photoelectric: 230VAC, 115VAC, 24VAC, 24VDC	
<b>SMOKE SENSOR MODEL NUMBER:</b>	55000-335DCT	
<b>SAMPLING TUBES:</b>	FAST Tube	Sectional sampling tube, kit fits up to 90" duct width
	STN-1.0	Sampling tube for 6" to 12" duct width
	STN-2.5	Sampling tube for 1' to 3' duct width
	STN-5.0	Sampling tube for 3' to 5' duct width
<b>POWER REQUIREMENTS:</b> (without accessories)	230VAC	12 mA
<b>Standby:</b>	115VAC	22 mA
	24VAC	55 mA
	24VDC	14 mA
<b>Alarm:</b>	230VAC	18 mA
	115VAC	32 mA
	24VAC	190 mA
	24VDC	68 mA
<b>RELAY CONTACT RATING:</b>		
<b>Alarm Contacts:</b>	Resistive load: 2 sets form "C" rated at 10 Amps @ 115VAC	
	Resistive load: 1 set form "A" rated at 2 Amps	
<b>Trouble Contacts:</b>	Resistive load: 1 set form "C" rated at 10 Amps @ 115VAC	
<b>AIR VELOCITY:</b>	100 to 4,000 ft./min.	
<b>AMBIENT TEMPERATURE:</b>	RT-3000-P -4°F to 140°F (-20°C to 60°C)	
<b>HUMIDITY:</b>	10% to 93% RH (@32°C) Non-Condensing / Non-Freezing	
<b>WIRING:</b>	Solid or stranded: #14 to #24 AWG terminals	
<b>APPROVALS:</b>	UL & CUL Listed (UL268A, UROX, UROX7) File # S2829 CSFM Listed (3240-1004:105)	
<b>MATERIAL:</b>	Grey plastic backbox, white plastic cover (Makrolon 94V-0)	
<b>DIMENSIONS:</b>	13 ½" L x 5 ½" W x 2 ¼" H	
<b>MAX. NET WT.:</b>	3 ½ lbs.	
<b>HARDWARE:</b>	7" exhaust tube, FAST Tube sectional sampling tube starter, sampling tube end cap, mounting template, test magnet, and mounting hardware included	

## ACCESSORIES

<b>MSR-100 series</b>	Remote Stations (test reset function)	<b>TG-2000</b>	Solo Smoke Gas w/TestPort Nozzle
<b>MSR-50 series</b>	Remote Stations (test reset function)	<b>TG-2500</b>	Centurion Smoke Gas w/TestPort Nozzle
<b>MS- series</b>	Remote Stations (push button & key reset)	<b>T-PB series</b>	Power supplies, 24VAC from 115VAC @1.0A input

### TECH SUPPORT:

[apcfire.com/support](http://apcfire.com/support)

### ENGINEERS & ARCHITECTS SPECIFICATIONS:

[apcfire.com/specifications](http://apcfire.com/specifications)

### FOR MORE PRODUCTS AND INSTALL GUIDES VISIT:

[apcfire.com/products](http://apcfire.com/products)

